

TM-192 / TM-192D (Datalogger)

Three-Axis Magnetic Field Meter (Gauss Meter)



Specifications :

- Display : 4 digits LCD, maximum reading 9999.
- Range : 20 / 200 / 2000 mG, 2 / 20 / 200 μ T
- Resolution : 0.01 / 0.1 / 1 mG or 0.001 / 0.01 / 0.1 μ T
- Accuracy :
 - $\pm(2.5\%+5\text{dgt})$ at 50Hz / 60Hz
 - $\pm(5.0\%+5\text{dgt})$ at 30Hz ~ 2000Hz.
- Sensor : Triple Axis
- Frequency response : 30Hz to 2000Hz.
- Sample rate : 2.5 times per second
- Battery : 9V NEDA 1604, IEC 6F22 or JIS 006P
- Battery life : Approximate 100 hours
- Operating temperature & humidity :
 - 5 $^{\circ}$ C to 40 $^{\circ}$ C, below 80% RH.
- Weight : About 230g.
- USB interface (TM-192D).
- 9999 Records data logger (TM-192D).
- Dimension : 173(L) x80(W) x32(H)mm.

TM-191

Magnetic Field Meter (Gauss Meter)



Protection Holster
(optional accessory)

Specifications :

- Display :
 - 3 $\frac{1}{2}$ digits LCD, maximum reading 1999.
- Range :
 - 200/2000 mG, 20/200 μ T.
- Resolution :
 - 0.1/1 mG or 0.01/0.1 μ T.
- Frequency response :
 - 30Hz to 300Hz.
- Sensor : Single Axis.
- Accuracy :
 - $\pm(2.5\%+6\text{dgt})$ at 50Hz/60Hz.
- Sample rate :
 - 2.5 times per second.

- Battery : 9V NEDA 1604, IEC 6F22 or JIS 006P.
- Battery life : Approximate 200 hours.
- Weight : About 180g.
- Dimension : 130(L) X56(W) X38(H)mm.
- Operating temperature & humidity :
 - 5 $^{\circ}$ C to 40 $^{\circ}$ C, below 80% RH.

TM-760

Mini Pocket Gauss Meter

(0~100mG)



Specifications :

- Magnetic Field : Single
- Frequency : 50Hz / 60Hz
- Magnetic Field Range :
 - 2.5~10mG / 20~100mG
- Display : 10 LEDs.
- Accuracy : 2.5% +6dgt.
- Power :
 - 2 batteries 1.5V AAA.
- Weight : Approx. 80g.
- Dimension :
 - 108(L)*48(W)*23(H)mm.

